

ELMA MOTORS



Data Sheet				No.		
Three Phase Induction Motor				Drawing No.		
Customer						
Client reference						
Type:		EM3-280S-4 75KW 400 690V 50HZ				
Brand		Elma			Date 20-11-2013	
Identification						
Frame:	280	mm	Insulation Class:	F		
Output:	75	kW	Temperature Rise:	47.6K		
Frequency:	50	Hz	Service Factor:	1,00		
Poles:	4	P	Duty:	S1		
Rated Speed:	1490	rpm	Ambient Temperature:	-20~+40°C		
Slip:	0,7	%	Altitude:	1000m		
Rated Voltage:	400	V	Protection Degree:	IP55		
Connection:	Δ		Cooling:	IC411		
Rated Current:	133,4	A	Mounting:	IM B3		
Rotor Voltage:			Vibration:	2.2 mm/s		
Connection:			Approx. Weight:	610	kg	
Rotor Current:			Moment of Inertia:	2,0828	kg/m2	
Locked Rotor Current:	746	%	Noise Level (Lp) :	82,3	dB(A)	
No Load Current:			Direction of Rotation:	Both		
Rated Torque:	480,7	Nm	Starting Method:	DOL	Y/D	VFD soft -st
Locked Rotor Torque:	254	%	Coupling:	DIRECT		
Breakdown Torque:	316	%	Colour	RAL 7031		
			Load Type:	Constant torque / Quadratical torque		
Performance				efficiency class IE3		
Output:	50%	75%	100%	Bearing Information		
Efficiency(%) :	95,3	95,9	95,89	Bearing:	DE	NDE
Power Factor:	0,71	0,81	0,846	Regreasing int.(h):	6317C3	6317C3
				Grease amount(g)	3500	3500
				Grease-PolyrexEM	37	37
				Caltex SRI-2	Caltex SRI-2	Caltex SRI-2
Notes / Accessories				Cassification		
Winding : 3XPTC150°C				attest		
Heaters, 230V 50Hz				3.1 3.2		
				Bureau Veritas	n.a.	n.a.
				Germanischer Lloyd	n.a.	n.a.
				Lloyds register of shipping	n.a.	n.a.
				RINA	n.a.	n.a.
				DNV	n.a.	n.a.
				Other	n.a.	n.a.
Standards				PRELIMINARY DOCUMENT		
Specification:	IEC60034-1 / GB755					
Test:	IEC60034-2-1 / GB/T1032					
Noise:	IEC60034-9 / GB10069.3					
Vibration:	IEC60034-14 / GB10068					
Edition						
Performed		Checked		Date		
Item	Changes			Performed	Checked	Date