

ELMA MOTORS



Data Sheet				No.		
Three Phase Induction Motor				Drawing No.		
Customer						
Client reference						
Type:				EM2-280M-2 90KW 400 690V 50HZ		
Brand				Elma Date 12-11-2013		
Identification						
Frame:	280	mm	Insulation Class:	F		
Output:	90	kW	Temperature Rise:	68.9K		
Frequency:	50	Hz	Service Factor:	1,00		
Poles:	2	P	Duty:	S1		
Rated Speed:	2975	rpm	Ambient Temperature:	-20~+40°C		
Slip:	0,8	%	Altitude:	1000m		
Rated Voltage:	400	V	Protection Degree:	IP55		
Connection:	Δ		Cooling:	IC411		
Rated Current:	152	A	Mounting:	IM B3		
Rotor Voltage:			Vibration:	2.2 mm/s		
Connection:			Approx. Weight:	570 kg		
Rotor Current:			Moment of Inertia:	0,765 kg/m2		
Locked Rotor Current:	670	%	Noise Level (Lp) :	84 dB(A)		
No Load Current:			Direction of Rotation:	CW		
Rated Torque:	288,9	Nm	Starting Method:	DOL Y/D VFD soft -st		
Locked Rotor Torque:	240	%	Coupling:	DIRECT		
Breakdown Torque:	260	%	Colour	RAL 7031		
			Load Type:	Constant torque / Quadratical torque		
Performance			efficiency class IE2			
Output:	50%	75%	100%	Bearing Information		
Efficiency(%) :	93,5	94,2	94,11	DE	NDE	
Power Factor:	0,82	0,88	0,909	Bearing:	6314C3 6314C3	
				Regreasing int.(h):	2000 2000	
				Grease amount(g)	27 27	
				Grease-PolyrexEM	Caltex SRI-2 Caltex SRI-2	
Notes / Accessories			Cassification			
Winding : 3XPTC150°C			attest			
Heaters, 230V 50Hz			3.1 3.2			
			Bureau Veritas	n.a.	n.a.	
			Germanischer Lloyd	n.a.	n.a.	
			Lloyds register of shipping	n.a.	n.a.	
			RINA	n.a.	n.a.	
			DNV	n.a.	n.a.	
			Other	n.a.	n.a.	
Standards				PRELIMINARY DOCUMENT		
Specification:	IEC60034-1 / GB755					
Test:	IEC60034-2-1 / GB/T1032					
Noise:	IEC60034-9 / GB10069.3					
Vibration:	IEC60034-14 / GB10068					
Edition						
Performed		Checked	Date			
Item	Changes			Performed	Checked	Date