

ELMA MOTORS



| Data Sheet | | | | No. | |
|-----------------------------|-------------------------|--------------------------------|-----------------------------|--------------------------------------|---------------------------|
| Three Phase Induction Motor | | | | Drawing No. | |
| Customer | | | | | |
| Client reference | | | | | |
| Type: | | EM2-132S-4 5.5KW 400 690V 50HZ | | | |
| Brand | | Elma | | Date 20-11-2013 | |
| Identification | | | | | |
| Frame: | 132 | mm | Insulation Class: | F | |
| Output: | 5,5 | kW | Temperature Rise: | 53K | |
| Frequency: | 50 | Hz | Service Factor: | 1,00 | |
| Poles: | 4 | P | Duty: | S1 | |
| Rated Speed: | 1455 | rpm | Ambient Temperature: | -20~+40°C | |
| Slip: | 3,0 | % | Altitude: | 1000m | |
| Rated Voltage: | 400 | V | Protection Degree: | IP55 | |
| Connection: | Δ | | Cooling: | IC411 | |
| Rated Current: | 11,1 | A | Mounting: | IM B3 | |
| Rotor Voltage: | | | Vibration: | 1.6 mm/s | |
| Connection: | | | Approx. Weight: | 68 | kg |
| Rotor Current: | | | Moment of Inertia: | 0,0205 | kg/m ² |
| Locked Rotor Current: | 700 | % | Noise Level (Lp) : | 57,4 | dB(A) |
| No Load Current: | | | Direction of Rotation: | Both | |
| Rated Torque: | 36,1 | Nm | Starting Method: | DOL Y/D VFD soft -st | |
| Locked Rotor Torque: | 250 | % | Coupling: | DIRECT | |
| Breakdown Torque: | 280 | % | Colour | RAL 7031 | |
| | | | Load Type: | Constant torque / Quadratical torque | |
| Performance | | | efficiency class IE2 | | |
| Output: | 50% | 75% | 100% | Bearing Information | |
| Efficiency(%) : | 87,0 | 88,3 | 87,98 | DE | NDE |
| Power Factor: | 0,61 | 0,74 | 0,81 | Bearing: | 6308ZZ/C3 6308ZZ/C3 |
| | | | | Regreasing int.(h): | |
| | | | | Grease amount(g) | |
| | | | | Grease-PolyrexEM | Caltex SRI-2 Caltex SRI-2 |
| Notes / Accessories | | | Cassification | | |
| Winding : 3XPTC150°C | | | attest | | |
| Heaters, 230V 50Hz | | | 3.1 3.2 | | |
| | | | Bureau Veritas | n.a. | n.a. |
| | | | Germanischer Lloyd | n.a. | n.a. |
| | | | Lloyds register of shipping | n.a. | n.a. |
| | | | RINA | n.a. | n.a. |
| | | | DNV | n.a. | n.a. |
| | | | Other | n.a. | n.a. |
| Standards | | | PRELIMINARY DOCUMENT | | |
| Specification: | IEC60034-1 / GB755 | | | | |
| Test: | IEC60034-2-1 / GB/T1032 | | | | |
| Noise: | IEC60034-9 / GB10069.3 | | | | |
| Vibration: | IEC60034-14 / GB10068 | | | | |
| Edition | | | | | |
| Performed | Checked | Date | | | |
| | | | | | |
| Item | Changes | | Performed | Checked | Date |
| | | | | | |
| | | | | | |
| | | | | | |
| | | | | | |